

Accessories for Actuated Valves

Type 40060 - Solenoid Valve



3/2 way Solenoid Valve

direct acting solenoid valve DN3, fast acting, body in brass, protecting class IP65, with cable plug for cable-Ø7 mm, circuit function: power free - outlet balanced, Pressure range 0 - 10.0 bar, Voltage tolerance ±10%, with flat seal and fixing screw

Port connection 1/4" G (BSPP) thread: X= 0

Port connection 1/4" NPT thread: X= 6

Version with NBR sealing

for neutral medium like air and water

Medium temperature: 0°C / 32°F up to +80°C / 176°F

Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

Part No. 40060.020X.C24A000 - Operating voltage 24V, AC (50Hz)

Part No. 40060.020X.C11A000 - Operating voltage 110V, AC (50Hz)

Part No. 40060.020X.C23A000 - Operating voltage 230V, AC (50Hz)

Part No. 40060.020X.C24D000 - Operating voltage 24V, DC

Part No. 40060.020X.C48D000 - Operating voltage 48V, DC

Version with EPDM sealing

for oil and fat-free medium

Medium temperature: -30°C / -22°F up to +90°C / 194°F

Ambient temperature: -30°C / -22°F up to max. +55°C / 131°F

Part No. 40060.020X.C24A00E - Operating voltage 24V, AC (50Hz)

Part No. 40060.020X.C11A00E - Operating voltage 110V, AC (50Hz)

Part No. 40060.020X.C23A00E - Operating voltage 230V, AC (50-60Hz)

Part No. 40060.020X.C24D00E - Operating voltage 24V, DC

Part No. 40060.020X.C48D00E - Operating voltage 48V, DC

Version with FKM sealing

for neutral medium like air and water

Medium temperature: 0°C / 32°F up to +90°C / 194°F

Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

Part No. 40060.020X.C24A0AF - Operating voltage 24V, AC (50Hz)

Part No. 40060.020X.C11A0AF - Operating voltage 110V, AC (50Hz)

Part No. 40060.020X.C23A0AF - Operating voltage 230V, AC (50Hz)

Part No. 40060.020X.C24D0AF - Operating voltage 24V, DC

Part No. 40060.020X.C48D0AF - Operating voltage 48V, DC

Version with FKM sealing, cleaned and degreased, suitable for oxygen

Part No. 40060.020X.C24AO2F - Operating voltage 24V, AC (50Hz)

Part No. 40060.020X.C11AO2F - Operating voltage 110V, AC (50Hz)

Part No. 40060.020X.C23AO2F - Operating voltage 230V, AC (50Hz)

Part No. 40060.020X.C24DO2F - Operating voltage 24V, DC

Part No. 40060.020X.C48DO2F - Operating voltage 48V, DC

Available options - on request only:

- other port connection (G1/8), body and seat material 1.4401
- circuit functions: power free - outlet pressure loaded

Standard
version

