

Accessories for Actuated Valves

Type 41060 - Solenoid Valve



3/2 way Solenoid Valve, including fixing accessories

direct acting solenoid valve DN3, fast acting, body in brass, protecting class IP65, with cable plug for cable-Ø7 mm, circuit function: power free - outlet balanced, Pressure range 0 - 10.0 bar, Voltage tolerance ±10%, with flat seal and fixing screw

Version with NBR sealing

port connections G (BSPP) 1/4 female thread, for neutral medium like air and water
Medium temperature: 0°C / 32°F up to +80°C / 176°F
Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

for actuators type 27511 and 27521

- Part No. 41060.0200.C24A000** - Operating voltage 24V, AC (50Hz)
- Part No. 41060.0200.C11A000** - Operating voltage 110V, AC (50Hz)
- Part No. 41060.0200.C23A000** - Operating voltage 230V, AC (50Hz)
- Part No. 41060.0200.C24D000** - Operating voltage 24V, DC
- Part No. 41060.0200.C48D000** - Operating voltage 48V, DC

for actuators type 27512 and 27522

- Part No. 41060.0210.C24A000** - Operating voltage 24V, AC (50Hz)
- Part No. 41060.0210.C11A000** - Operating voltage 110V, AC (50Hz)
- Part No. 41060.0210.C23A000** - Operating voltage 230V, AC (50Hz)
- Part No. 41060.0210.C24D000** - Operating voltage 24V, DC
- Part No. 41060.0210.C48D000** - Operating voltage 48V, DC

for actuators type 27514

- Part No. 41060.0220.C24A000** - Operating voltage 24V, AC (50Hz)
- Part No. 41060.0220.C11A000** - Operating voltage 110V, AC (50Hz)
- Part No. 41060.0220.C23A000** - Operating voltage 230V, AC (50Hz)
- Part No. 41060.0220.C24D000** - Operating voltage 24V, DC
- Part No. 41060.0220.C48D000** - Operating voltage 48V, DC

for actuators type 27515

- Part No. 41060.0230.C24A000** - Operating voltage 24V, AC (50Hz)
- Part No. 41060.0230.C11A000** - Operating voltage 110V, AC (50Hz)
- Part No. 41060.0230.C23A000** - Operating voltage 230V, AC (50Hz)
- Part No. 41060.0230.C24D000** - Operating voltage 24V, DC
- Part No. 41060.0230.C48D000** - Operating voltage 48V, DC

Version with EPDM sealing

port connections G (BSPP) 1/4 female thread, for oil- / degrease-free medium
Medium temperature: -30°C / -22°F up to +90°C / 194°F
Ambient temperature: -30°C / -22°F up to max. +55°C / 131°F

for actuators type 27511 and 27521

- Part No. 41060.0200.C23A00E** - Operating voltage 230V, AC (50Hz)
- Part No. 41060.0200.C24D00E** - Operating voltage 24V, DC

for actuators type 27512 and 27522

- Part No. 41060.0210.C23A00E** - Operating voltage 230V, AC (50Hz)
- Part No. 41060.0210.C24D00E** - Operating voltage 24V, DC

for actuators type 27514

- Part No. 41060.0220.C23A00E** - Operating voltage 230V, AC (50Hz)
- Part No. 41060.0220.C24D00E** - Operating voltage 24V, DC

for actuators type 27515

- Part No. 41060.0230.C23A00E** - Operating voltage 230V, AC (50Hz)
- Part No. 41060.0230.C24D00E** - Operating voltage 24V, DC

Available options - on request only:

- other port connections (1/4"NPT, G1/8), body and seat material 1.4401
- circuit functions: power free - outlet pressure loaded

Standard version

